

# AWUS036NHR<sub>v2</sub>

## 802.11b/g/n Long-Rang USB Adapter

AWUS036NHRv2 is the IEEE 802.11b/g/n Wireless USB adapter provides users to launch IEEE 802.11b/g/n wireless network at 150 Mbps in the 2.4GHz band, which is also compatible with IEEE 802.11b/g wireless devices at 54 Mbps. You can configure AWUS036NHRv2 with ad-hoc mode to connect to other 2.4GHz wireless computers, or with Infrastructure mode to connect to a wireless AP or router for accessing to Internet.

AWUS036NHRv2 includes a convenient Utility for scanning available networks and saving preferred networks that users usually connected with. Security encryption can also be configured by this utility.

**ALFA**  
NETWORK  
Your Source of Hardware



For further details:

Alfa Network Inc.,  
4F-1 No. 106, Rueiguang Rd.,  
Neihu District,  
Taipei City, Taiwan.  
<http://www.alfa.com.tw>  
[sales@alfa.com.tw](mailto:sales@alfa.com.tw)  
Tel:+886-2-27968477 | Fax:+886-2-27968478

# AWUS036NHR<sub>v2</sub>

## 802.11b/g/n Long-Rang USB Adapter

### Features

- Compatible with IEEE 802.11n, 802.11b/g/n wireless standards
- 2.4GHz frequency band, MIMO (Multiple Input Multiple Output)
- Complies with Universal Serial Bus Rev. 2.0 specifications
- High speed data rate up to 150 Mbps
- Supports wireless data encryption with 64/128-bit WEP, WPA, WPA2, TKIP, AES
- Wide Range coverage
- Support software AP
- Compliant with FCC Part 15.247 for US, ETS 300 328 for Europe
- Supports driver for Windows 2000, XP 32/64, Vista 32/64, Windows 7 /8
- Mac (10.4.x/10.5.x/10.6.x/10.7.X/10.8.X) Power PC& PC.

### Specification

Standards	Wireless: IEEE 802.11b/g/n
Data Rate	802.11b: UP to 11Mbps : UP to 54Mbps 802.11n: UP to 150Mbps
OS Supported	Windows 2000, XP, Vista, 7,8 Mac 10.4, 10.5, 10.6,10.7,10.8 Support S/W AP
Interface	USB 2.0 mini USB
Antenna Type	1 x 2.4Ghz RP-SMA connector
Chipset	RTL8188RU
Antenna	5dBi 2.4GHz Antenna
Frequency Range	2.412 ~ 2.483 GHz
Channels	1~11 channels ( North America ) 1~13 channels ( General Europe ) 1~14 channels (Japan)
Sensitivity	11b: -92dBm : -76dBm 11n: -73dBm@HT20 -70dBm@HT40
Data Modulation Type	BPSK,QPSK, CCK and OFDM
Power	Voltage: 5V+5%
Security	WEP 64/128, 802.1X support, Wi-Fi Protected Access (WPA), WPA-PSK, WPA II-PSK, Cisco CCX support, WAPI-PSK, WAPI-CERT
Operating Temp	0°C ~ 50°C
Storage	-10°C ~ 65°C
Humidity	5% ~ 98% non-condensing

